

## Marten masonry primer

610

**Description** Pigmented water born primer, based on acrylic emulsion , with good sealing and binding properties.

### Principal uses

- For interior and exterior use.
- Good impregnation properties.
- Good sealing and adhesion on very porous substrates.
- Water vapor permeable.
- Unsaponifiable and alkali resistant.
- Good drying properties and almost odorless.
- Easy to apply.

**Substrate** Concrete , masonry , cement rendering , plaster , etc.

### Characteristics

**Color** : White- or according to Martensons color card

**Finish** : Flat

**Specific gravity** : Approx. 1.02 g /cm<sup>3</sup>

**Volume solids ( % )** : Approx. 12 - 14 %

**Theoretical coverage** : Approx 8 - 9 m<sup>2</sup> / lt.

Depend upon substrate condition and method of application .

**Drying time** : Approx. 1 hour

**Overcoat interval** : Min. 3 hours

**Shelf life** : 12 months, from the date of production,  
( Stored in a dry and cool place) .

### Surface preparation and condition

New and previously painted surfaces should be dry and free from all loose and flaking materials, dirt, grease , wax, and similar contamination.

Used as a primer coat in an emulsion or texture system.

### Application guide line

#### Instrument for use

#### ( Brush and Roller )

volume of thinner : Approx. 5 – 10 %

recommended thinner : pure water

**Cleaning Solvent** : pure water