

Marten Acrylic Sealer 611

Description Premium quality pigmented primer sealer, based on copolymer acrylic emulsion resin, designed for cold, hot, and humid climates.

Principal uses

- For interior and exterior use.
- Good foundation coat for various emulsion and texture system
- V. Good sealing properties.
- V. Good adhesion properties.
- Water vapor permeable.
- Unsaponifiable and alkali resistant.
- Quick drying properties and almost odorless.
- Easy to apply.

Substrate Concrete, masonry, cement rendering, plaster, etc.

Characteristics

Color : White – or according to Martensons color card
Finish : Flat
Specific gravity : Approx. 1.29 g /cm³
Volume solids (%) : Approx 24 - 25 %
Theoretical coverage : Approx 10 m² / lt.
Depends upon substrate condition and method of application .
Drying time : Approx. 1 hour
Overcoat interval : Min. 4 hours
Shelf life : 12 months from the date of production,
(stored in a dry and cool place).

Surface preparation and condition :

- New and previously painted surfaces should be dry and free from all loose and flaking materials, dirt, grease , wax, and similar contamination.
- Used as a primer coat in an emulsion or texture system.
- Premium quality acrylic primer sealer , used to seal and reduce the porosity of substrate.

Application guide line

Instrument for use

(Brush and Roller)

volume of thinner : approx. 5 – 10 %
recommended thinner : pure water
Cleaning Solvent : pure water