

Graffito 2 mm 650

Description A one-coat wall cover texture, based on flexible and weather resistance copolymer dispersion, filled with ground natural stone.

Principal uses

- For interior and exterior use.
- Good weather resistance.
- Good hiding flexibility.
- Good adhesion properties.
- Good color retention properties.
- Unsaponifiable and alkali resistance
- Outstanding impact resistance.
- Can be used to create a variety of texture patterns.
- Almost odorless.
- Easy to apply.

Characteristics

- Color : White / or as per Martenson color card
- Specific gravity : Approx. 1.85 g /cm³
- Volume solids (%) : Approx. 75 %
- Theoretical coverage : Approx. 3 - 4kg/m²
Depends upon substrate condition and method of application
- Drying time : Approx. 3 – 4 hours.
- Overcoat interval : Min. overnight.
- Shelf life : 12 months from date of application
(Stored in a dry and cool place)

Surface preparation

- New and previously painted surfaces should be dry and free from all loose and flaking materials, dirt, grease , wax, and similar contaminationPaint systems advice

For new substrate:

- New concrete (plaster must be dry wait 3 to 5 weeks before application).
- All dirt , powder and other contamination must be removed
- Apply one coat of () Marten Masonry primer, or () Marten Acrylic sealer.
- Gypsum containing materials and substrate which are powdery should be primed with one coat of (Marten alkali resistant Primer

For previously painted substrates:

- Remove all cracked, brittle and poorly adhering paint and any other contamination .
- Good intact wall paint layers must be cleaned with a 3 % solution of ammonia in Water.
- Glossy paint layers must be sanded properly.
- Not recommended on old Alkyd types of wall paint.

Application guide line

Instrument for use

(TOOLS)

:Stainless steel for application.
Plastic trowel for structuring . Has to be roughened before use.

Recommended thinner

: not recommended

Cleaning Solvent

: pure water