

Marten Texture Gloss 653

Description Premium quality texture gloss, based on synthetic emulsion resin, and weather resisting pigments.

Principal uses

- For interior and exterior use.
- Good resistance to wet cleaning and scrubbing.
- Good color and gloss retention.
- Good weather resistance.
- High flexibility.
- Unsaponifiable and alkali resistance.
- Can be used to create a variety of texture patterns.
- Almost odorless.
- Easy to apply.

Characteristics

Color : White / or as per Martenson color card

Specific gravity : Approx. 1.17 g /cm³

Volume solids (%) : Approx. 35 - 36 %

Theoretical coverage : Approx. 10 – 12 m²/lt. On 30 µm DFT
Depends upon substrate condition and method of application .

Drying time : Approx. 2 hours.

Overcoat interval : Min. 8 hours

Shelf life : 12 months from date of application
(Stored in a dry and cool place)

Surface preparation:

- New and previously painted surfaces should be dry and free from all loose and flaking materials, dirt, grease , wax, and similar contamination

Paint systems advice

For new substrate:

- New concrete (plaster must be dry wait 3 to 5 weeks before application).
- All dirt , powder and other contamination must be removed
- Ensure cement based and plastered surfaces are dry and properly cleaned and sufficiently dry max, 4% moisture.
- All dirt, powder and other contamination must be removed.
- Apply one coat of (610) Marten Masonry primer, or (611) Marten Acrylic sealer - Gypsum containing materials and substrate, which are powdery, should be primed with one coat of (612) Marten alkali resistant Primer .

For previously painted substrates:

- Remove all cracked, brittle and poorly adhering paint and any other contamination .
- Good intact wall paint layers must be cleaned with a 3 % solution of ammonia in Water.
- Glossy paint layers must be sanded properly.
- Not recommended on old Alkyd types of wall paint.

Application guide line

Instrument for use

(Brush and Roller)

Instruments : Various types can be used to provide different patterns.

Volume of thinner : 0 – 5 %

Recommended : pure water.

Cleaning Solvent : pure water