

Marten Aluminum Paint 660

Description Premium quality aluminum finishes, based on alkyd resin, pigmented with a high proportion of leafing aluminum for light and heat reflectance.

Principal uses

- For interior and exterior use.
- Good heat and light reflecting properties.
- Good covering and hiding capacity.
- Good drying properties.
- Good weather resistance.
- Lead free.
- Good durability.
- Easy to apply.

Characteristics

Color : Silver finish.
Finish : Metallic
Specific gravity : Approx. 0.88 g /cm³
Volume solids (%) : Approx. 33 - 35 %
Theoretical coverage : Approx. 11 – 12 m² / lt.
Depends upon substrate condition and method of application .
Drying time : Approx. 1 hour.
Overcoat interval : Min. 6 – 8 hours
Shelf life : 24 months from the date of production
(Stored in a dry and cool place).

Surface preparation and condition

Should be stable , firm, dry and free from laitance , dust, and loose old paint, dirt, grease, and contamination.

- Prime with one coat of (613) Marten red oxide primer
- Metal (non ferrous – aluminum, Galvanized, Stainless steel copper, etc)
- Should be primed with 1 coat of etch primer.

Application guide line

Instrument for use

(Brush / and roller)

Volume of thinner : Not required.
Recommended thinner : Enamel reducer TN - 01

(Airless spray)

Volume of thinner : 0 – 5 %.
Recommended thinner : Enamel reducer TN - 01

Cleaning Solvent : Enamel reducer TN - 01