

Marten Varnish Gloss 661

Description Premium quality clear varnish gloss finishes based on synthetic alkyd resin

Principal uses

- For interior and exterior use.
- Very good hiding and covering capacity
- Very good flow and drying properties
- Very good gloss retention properties
- Very good color retention properties
- Developed to protect and decorate wood.
- Easy to apply.

Substrate Recommended for use on new and old woodwork.

Characteristics

Color : Clear
Finish : Gloss
Specific gravity : Approx. 0.90 g /cm³
Volume solids (%) : Approx. 29 - 30 %
Theoretical coverage : Approx .14 - 15m² / lt.
Depends upon substrate condition and method of application .
Drying time : Approx. 4 – 5 hours.
Overcoat interval : Min. overnight.
Shelf life : 24 hours from the date of production
(Stored in a dry and cool place).

Surface preparation and condition

- New and previously painted surfaces should be dry and free from laitance and loose old paint, dirt, grease, wax, and similar contamination.
- Moisture in the wood should be tested before application, and must not be higher than 17%.

For application with wood stain, after surface preparation and sanding, first coat should be stained with (614) Marten wood stain

- Second coats to be applied with (661) Marten varnish gloss diluted 5% with recommended reducer.
- Third coat should be (661) Marten varnish gloss undiluted.
- If surface applied only with varnish, first coat should be diluted 20% with recommended thinner.
- Second coat should be diluted 10%, with recommended reducer
- Third coat should be applied without any dilution.

Application guide line

Instrument for use

(Brush)

Volume of thinner : approx. 5 – 10 %
Recommended thinner : Enamel reducer TN - 01

Cleaning Solvent : Enamel reducer TN - 01