

Marten Wood Stain 662

Description Premium quality wood stain finishes based on urethane alkyd resin and organic dyes.

Principal uses

- For interior and exterior use.
- Developed to protect and decorate wood.
- Very good color retention properties
- Good drying properties.
- Good penetrating properties.
- Easy to apply.

Substrate Recommended for use on new and old woodwork.

Characteristics

Color : Martensons wood stain color card.
Finish : Matt
Specific gravity : Approx. 0.82 g /cm³
Volume solids (%) : Approx. 4 - 5 %
Theoretical coverage : Approx .10 - 11m² / lt.
Depends upon substrate condition and method of application .
Drying time : Approx. 10 – 15 hours.
Overcoat interval : Min. 3 – 4 hours.
Shelf life : 24 hours from the date of production
(Stored in a dry and cool place).

Surface preparation and condition

- New and previously painted surfaces should be dry and free from laitance and loose old paint, dirt, grease, wax, and similar contamination.
- Moisture in the wood should be tested before application, and must not be higher than 17%.

For application with wood stain, after surface preparation and sending, fist coat should be stained with (662) Marten wood stain

- Second coats to be applied with (661) Marten varnish gloss diluted 5% with recommended reducer.
- Third coat should be (661) Marten varnish gloss undiluted.

If surface applied only with varnish, first coat should be diluted 20% with recommended thinner.

- Second coat should be diluted 10%, with recommended reducer
- Third coat should be applied without any dilution.

Application guide line

Instrument for use

(Brush)

Volume of thinner : Not required

Cleaning Solvent : Enamel reducer TN - 01