

Marten Road Mark 663

Description Good quality road mark paint , based on high build synthetic alkyd resin .

Principal uses

- For interior and exterior use.
- Good hiding and covering capacity
- Good flow and drying properties
- Good resistance against water and oil.
- Good adhesion to concrete and asphalt.
- Easy to apply.

Substrate Concrete, asphalt road and runways

Characteristics

Color : White – black - yellow
Finish : Flat
Specific gravity : Approx. 1.50 g /cm³
Volume solids (%) : Approx. 45 - 47 %
Theoretical coverage : Approx. 9 - 10 m² / lt. For (50µm)
Depends upon substrate condition and method of application .
Drying time : Approx. 1 hour
Overcoat interval : Min. overnight
Shelf life : 24 months from the date of production
(Stored in a dry and cool place).

Surface preparation and condition

- New and previously painted surfaces should be dry and free from all loose and flaking materials, dirt, grease, wax, and similar contamination.
- Asphalt surface must be free from any contamination, and must be aged for at least 6 months.

Application guide line

Instrument for use

(Brush and Roller)

Volume of thinner : approx.5 – 10 %
Recommended thinner : Enamel reducer TN – 01

(Air spray)

Volume of thinner : approx.0 – 5 %
Recommended thinner : Enamel reducer TN - 01

Cleaning Solvent : Enamel reducer TN - 01